## **MAM-003S**



MAM-003S has a holding force of 500 kg and the magnetic component is encapsulated in a stainless steel housing for enhanced corrosion resistance and durability for longer periods of sea water exposure.



The Miko Anchor Magnets form a series of powerful and robust underwater fixing points. With holding forces ranging from 90 kg to 2 000 kg, these magnets are used worldwide for a wide range of applications. The MAM-003S can be used to fasten and secure tools and equipment to ship sides, and other steel structures. On account of the stainless steel housing, the magnet is also able to stay fastened for longer periods of time. The MAM-003S is equipped with a mooring lug and breaking lever for easy release and safe operation. The bottom is fitted with a rubber filling for increased friction and improved usability.

All Miko magnets are shipped in a double-skin steel box to isolate the magnetic field and to prepare them for air freight.

MAM-003S is also available in a watertight plastic case with built-in magnetic shielding.

Read "IMPORTANT NOTES ABOUT MIKO MAGNETS" enclosed in each box before use.



Case is optional

## SPECIFICATIONS

HOLDING FORCE 500 KG

**FOOTPRINT** 155 X 115 MM

**NET WEIGHT** 4 KG

**GROSS WEIGHT (BOX)** 7 KG

**DEPTH RATING** FULL OCEAN DEPTH

QUANTITY IN BOX 1 PCS

The stated holding force refers to the perpendicular holding force when applied directly onto a clean mild steel plate of minimum thickness 13 mm.

